

DCM305E

Earth Leakage Clampmeter



- **0.001 mA resolution**
- **Up to 100 A AC**
- **TRMS reading**
- **Low pass filter to aid stability of readings**
- **Auto, data & peak hold**
- **40 mm jaw**

DESCRIPTION

The DCM305E is designed to check earth leakage currents; however the upper range enables TRMS AC current measurements of up to 100 A. TRMS meters can measure both pure, undistorted, sinusoidal AC waveforms and non-sinusoidal AC waveforms which can contain pulse trains, triangles, spikes and other ragged waves.

The instrument has six ranges: 6 mA, 60 mA, 600 mA, 6 A, 60 A, 100 A with a minimum resolution of 0.001 mA on the 6 mA range. Either auto or manual ranging can be selected.

Harmonics / electrical noise on the cables / circuit under test can give rise to incorrect readings so the DCM305E features a low pass filter (50/60 Hz) which vastly improves measurements on these particular circuits.

A compare function is also featured which has 3 pre-set leakage limits (0.25, 0.50, 3.5 mA) which when selected offers a visual indication and audible warning when the pre-set limit is exceeded.

For those hard to read measurements, where accessibility is a problem, auto hold and data hold features have been incorporated to aid measurements. A peak hold option is also featured on this instrument.

An auto-backlight also aids easy viewing of the 6000 count display.

The 40 mm jaw has been designed to allow measurements on both insulated and non-insulated conductors.

Safety has been enhanced with inclusion of a tactile hand barrier / hand guard in the instrument case design.

To save battery life an automatic power off feature will switch the clamp off if no readings have been made during a 20 minute period.

The instrument is pocket sized, light weight, rugged and easy to use, making it an ideal choice for the electrical industry.

APPLICATIONS

A typical application for the DCM305E would be a measurement of earth leakage current in a circuit where the RCD keeps tripping out unexpectedly.

The measured result will quickly identify whether the earth leakage current present is excessive causing the RCD to trip or if the RCD itself is very sensitive / faulty. Earth leakage can be the result various undetected faults in the installation or a faulty appliance.

Cable insulation deterioration, cable damage or the ingress of moisture into areas where exposed terminals are present may give rise to earth leakage current.

FEATURES

- 0.001 mA resolution
- 100 A range for standard AC current measurements
- Compare feature
- Low pass filter
- Analogue bargraph display for trending

SPECIFICATIONS

Display: 6000 count
Measuring function: TRMS Leakage current and load current
Ranges: 6.000 mA / 60.00 mA / 600.00 mA / 6.000 A / 60.00 A / 100.0 A
Basic accuracy: ± (1.0 % + 3d)

AC Current:

Range	Resolution	Accuracy
6 mA	0.001 mA	0 ~ 10 A ±(1 % reading + 8 digits)
60 mA	0.01 mA	10 ~ 50 A
600 mA	0.1 mA	±(2 % reading + 10 digits)
6 A	0.001 A	50 ~ 100 A
60 A	0.01 A	±(10 % reading + 10 digits)
100 A	0.1 A	

Frequency response (61 ~ 400 Hz):

0 ~ 10 A
±(2 % reading + 11 digits)
10 ~ 50 A
±(10 % reading + 11 digits)
50 ~ 100 A
±(35 % reading + 11 digits)

Low Pass Filter

Range	Resolution	Accuracy
6 mA	0.001 mA	0 ~ 10 A ±(2 % reading + 8 digits)
60 mA	0.01 mA	10 ~ 50 A
600 mA	0.1 mA	±(3 % reading + 10 digits)
6 A	0.001 A	50 ~ 100 A
60 A	0.01 A	±(12 % reading + 10 digits)
100 A	0.1 A	

Accuracy specified at operating temperature:

23° C ± 5° C <80% RH

Resolution: 0.001 mA

Operating frequency range:

50 - 400 Hz

Sampling rate: 5 times / second

Data, auto, peak hold: User Selectable

Low pass filter: 50 / 60 Hz

Low pass filter cut-off frequency:

Approximately 100 Hz with an attenuation characteristic of approximately -24 dB / octave

Compare pre-set limits: 0.25, 0.50, 3.50 mA

Jaw size: 40 mm (750 mm conductor size)

Maximum jaw opening: 43 mm

Overload: "OL"



Low battery:

Auto power off: 20 minutes of inactivity

Operating temperature: 0 °C - 50 °C

Storage temperature: -20 °C - 60 °C

Operating Altitude: ≤2000 m

Temperature coefficient: 0.2 x (Spec. Accuracy) / °C, <18 °C, >28 °C

Power Supply: 2 x 1.5 V alkaline AAA / LR03

Battery life: 60 hours

Size: 78 mm (W) x 203 mm (H) x 42 mm (D)

Weight: 300 g

Safety: EN61010-1 CAT III 300 V

EMC: EN61326-1

ORDERING INFORMATION

Description	Part number	Description	Part number
Earth leakage clampmeter	2009-574	Included accessories	
		Carrying case	

SALES OFFICE

Megger Limited
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
E UKsales@megger.com

DCM305E_DS_en_V01

www.megger.com
ISO 9001
The word 'Megger' is a registered trademark



Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via de EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Ons moderne service- en kalibratielaboratorium beschikt over een RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



Kijk voor een overzicht van al onze diensten op euro-index.nl/diensten



Mobiele Service

Naast de vaste kalibratielaboratoria in Capelle aan den IJssel en Zaventem beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.nl) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen (individueel en klassikaal)
- Cursussen en workshops
- Demonstratie- en instructievideo's
- Whitepapers



Servicebalie



Onderhoud, reparatie en kalibratie



Cursussen en workshops



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® NL 21004



NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: 010 - 2 888 000
F: 010 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: +32 - (0)2 - 757 92 44
F: +32 - (0)2 - 757 92 64
info@euro-index.be
www.euro-index.be