

DET4TD2 and DET4TR2 Digital Ground Testers



- IP54 rated
- 2, 3 and 4 point testing
- Selectable 25 V or 50 V output
- Dry cell or rechargeable versions
- Simple one button operation
- Robust carry case

DESCRIPTION

Megger's DET4 family of ground testing instruments offers a unique solution to your ground rod and soil resistivity testing needs. The standard instrument comes with, test leads, stakes, terminal adaptors for bare wire, batteries and calibration certificate delivered in a tough polypropylene carry case - everything you need to start testing in one kit.

The ground testers are rated to IP54 making it truly an outdoor instrument. The ground tester has been designed to be easy to use, a large selector switch makes selection of 2 pole, 3 pole or 4 pole test easy with gloved hands - and the design makes the fitting of shorting links to perform 2 pole tests a thing of the past. A large, clear, easy to read LCD display and thumb sized test button again makes the instrument particularly suited to the outdoor conditions of ground testing.

In addition to this ease of use the ground tester also automatically checks the connection and condition of the P spike and the C spike, indicating the status on the display. The instrument also includes a voltmeter to allow you to measure the ground voltage. The ground tester can measure resistance from 0.01 Ω through to 20 k Ω and earth voltages up to 100 V. To allow testing in noisy environments the instrument is capable of rejecting noise of up to 40 V peak to peak.

The DET4TD2 digital ground tester is powered from 8 AA batteries which are widely available and deliver excellent testing time. The DET4TR2 is powered from rechargeable AA cells. The battery charger is built in and the instrument is supplied with an AC/DC adaptor. For both instruments, the battery status is displayed using a bar-graph.

The Megger ground testers comply with stringent safety standards and are rated to 100 V CAT IV. They also have selectable 25 V or 50 V output for compliance with IEC 61557-5.

DET4TD2 and DET4TR2 Digital Ground Testers

SPECIFICATIONS

| | |
|-------------------------------------------------|----------------------------------------------------------------------------------|
| IP rating | IP54 |
| C stake, P stake and noise check | Automatic |
| Noise rejection | 40 V peak to peak |
| 2 wire, 3 wire, 4 wire test | Yes, no shorting links required |
| Instrument output | |
| Voltage: | ±25 V or ± 50 V at 94 Hz, 105 Hz, 111 Hz and 128 Hz |
| Current: | 4.5 mA or 0.45 mA or 0.045 mA |
| Resistance range | 2, 3, 4 pole: 0.01 Ω to 200 kΩ |
| Maximum probe resistance | |
| R _p limit: | 100 kΩ (50 V output voltage) |
| R _c limit: | 100 kΩ (50 V output voltage) |
| Limits reduced to 50 kΩ for 25 V output voltage | |
| Limits reduced to 5 kΩ for 0.01 Ω resolution | |
| Earth / ground voltage range | 0 to 100 V ac |
| Earth / ground voltage accuracy | 2% ±2 V |
| Display | 3½ high contrast liquid crystal, backlit |
| Power supply | DET4T2 8 off AA (LR6) cells DET4TR2 8 off AA (LR6) NiMH rechargeable cells |
| Battery charger: | 100-240 VAC (50/60 Hz) |
| Operating temperature range and humidity | -15 to +55 °C (5 °F to 131 °F) |
| Storage temperature range and humidity | -40 to +70 °C (-40 °F to 158 °F) |

Safety

Complies with the requirements of IEC61010-1 100 V CAT IV between terminal pairs.

The CAT IV 100 V rating is dependant on the use of a leadset of at least this rating, for example the optional two wire leadset part number 1001-858.

EMC

In accordance with IEC61326-1

Compliance

Complies with the requirements of KEMA K85B.

Complies with the following parts of EN61557, "Electrical safety in low voltage distribution systems up to 1000 V a.c. and 1500 V d.c. - Equipment for testing, measuring or monitoring of protective measures".

Part 1 - General requirements

Part 5 - Resistance to earth

| | |
|-------------------|-------------------------|
| Dimensions | 203 mm x 148 mm x 78 mm |
| Weight | 1 kg |

DET4TD2 and DET4TR2 Digital Ground Testers

ORDERING INFORMATION

| Description | Part number | Description | Part number |
|--------------------------------------------------------------------|-------------|------------------------------------------------------------------------------------------------|-------------|
| Product | | Optional accessories | |
| DET4TD2 | DET4TD2 | Replacement hard carry case | 5410-429 |
| DET4TR2 (rechargeable) | 1000-324 | 2 replacement earth test spikes (200 mm, 8 mm dia.) | 6220-804 |
| Included accessories | | Replacement ground test leads (x4) for included kit (15 m, 10 m, 10 m, 3 m) | 6220-806 |
| Hard carry case | | Battery charger (DET4TCR2 only) | 6280-370 |
| Stake and wire kit (15 m, 10 m, 3 m) | | Calibration check box (25 Ohm) | 1000-435 |
| Right angle terminal adaptors (to connect bare wires to terminals) | | Right angled terminal adaptor set | 1012-511 |
| Battery charger (DET4TCR2 only) | | Black crocodile clip (1) | 6220-850 |
| | | ETK50 2 x 50 m, 2 x 30 m, complete with spikes and tape measure, in a weather proof holdall | 1010-177 |
| | | Vehicle 12 V socket charger (rechargeable versions only) | 6280-375 |
| | | 'Getting down to earth' A Megger guide to earth testing | 21500-072 |
| | | Leadset | 1001-858 |

SALES OFFICE

Megger Limited
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
E UKsales@megger.com

DET4TD2_DET4TR2_DS_en_V13

www.megger.com
ISO 9001

The word 'Megger' is a registered trademark

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via de EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Ons moderne service- en kalibratielaboratorium beschikt over een RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



Kijk voor een overzicht van al onze diensten op euro-index.nl/diensten



Mobiele Service

Naast de vaste kalibratielaboratoria in Capelle aan den IJssel en Zaventem beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.nl) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen (individueel en klassikaal)
- Cursussen en workshops
- Demonstratie- en instructievideo's
- Whitepapers



Servicebalie



Onderhoud, reparatie en kalibratie



Cursussen en workshops



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® NL 21004



NETHERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: 010 - 2 888 000
F: 010 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: +32 - (0)2 - 757 92 44
F: +32 - (0)2 - 757 92 64
info@euro-index.be
www.euro-index.be